

TYPE:

KEY FEATURES

- Highly effective noise absorption
- 3 sizes and a wide range of colors
- High performance dimmable LED light source (Direct) and optional upwards wash dimmable LED lighting (Indirect)
- Height adjustable 9' / 3m suspension cables and Black woven power cable
- IES photometric files available
- L70 lifetime rating of 50,000 hours
- Can be mounted flush to ceiling

OPTIONAL EXTRAS


Additional options available upon request:


- 0.1% dimming option
- POE
- Bluetooth controller (US & EU only)
- Tunable White output
- White canopy and power cord
- High-output direct-indirect (HO) lighting

Declare.

SIZE AND WEIGHT







	SMALL			MEDIUM			LARGE		
Output	Delivered Lumens	Wattage	Efficacy	Delivered Lumens	Wattage	Efficacy	Delivered Lumens	Wattage	Efficacy
Direct or Indirect	1634 lm	24 W	68 lm/W	5133 lm	58.9 W	87.2 lm/W	5133 lm	58.9 W	87.2 lm/W
Direct + Indirect	-	-	-	4997 lm	54.5 W	91.7 lm/W	4997 lm	54.5 W	91.7 lm/W
High-output Direct + Indirect	-	-	-	8609 lm	100.8 W	85 lm/W	8609 lm	100.8 W	85 lm/W
Weight	17.6 lbs / 8 Kg			30.8 lbs / 14 Kg			66.1 lbs / 30 Kg		

ORDER CODE


EXAMPLE: LX - VEC - L - R - 40 - DI - UNV - RD (Luxxbox Vapor Echo Cylinder, Large, Red, 4000K, Direct/Indirect output, Universal 1% dimming, Remote driver)

LX - VEC											
CODE	SIZE		COLOR	COLOR	R TEMP OUTPUT		DRIVER / DIMMING		DRIVER TYPE		
	s M	Small 19.5 x14.2" / 500x360mm Medium 30"x 17.7" / 762x450mm	Use color codes as shown	30 35 40	3000K 3500K 4000K	D I DI**	Direct Indirect Direct-Indirect	UNV G***	0 - 10V - 1% dimming (120-277V) (North America only) 1% dimming DSI/DALI (220 - 240V)	CD	Canopy concealed driver (UNV/North America only) Remote driver (UNV or G)
VEC 30 x 17.7 / 782x45011111 *E26 E26 Lamp holder - 120V AC (North America only) L arge *E27 Lamp holder - 220-240V AC (Global)				only)							
	НО	High-output Direct-Indirect	rect								

^{*} Please note the light globe or driver will not be supplied with the E26/E27 option for this fixture. | **Direct + Indirect option is not available for size S with an on-board driver configuration *** Global (G) dimming type is available with Remote driver (RD) only

AVAILABLE COLORS

Colors are subject to lead times and variations across batches.



Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. February 2024 . LX-Vapor-Echo-Cylinder.V2 v5.00



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM WWW.LUXXBOX.COM
















TYPE:

PHOTOMETRICS


	SMALL	MEDIUM / LARGE			
Outpuer Option	Direct OR Indirect	Direct OR Indirect	Direct + Indirect	High-output Direct + Indirect	
Total Lumens Delivered	1634 lm	5133 lm	4997 lm	8609 lm	
Wattage	24 W	58.9 W	54.5 W	100.8 W	
Efficacy	68 lm/W	87.2 lm/W	91.7 lm/W	85 lm/W	
CRI		90)+		
ССТ	3000-3500-4000 K				
UGR	<19				

LUMINOUS INTENSITY DISTRIBUTION

SMALL DIRECT OR INDIRECT



MEDIUM / LARGE DIRECT AND INDIRECT



TM-30METRICS


Fidelity Index (Rf): Average similarity to the reference source for all colors Gamut Index (Rg): Average change in chroma for all colors

	SMALL	MEDIUM/LARGE
Rf (Fidelity Index)	90	90.7
Rg (Gamut Index)	100	98.8

MEDIUM / LARGE DIRECT OR INDIRECT




MEDIUM / LARGE HIGH-OUTPUT DIRECT+INDIRECT




COLOR VECTOR GRAPHIC

SMALL



MEDIUM/LARGE



Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal, February 2024, LX-Vapor-Echo-Cylinder, V2 v5.00



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM LUXXBOX PTY LTD imes (P)+61 7 3257 2822 imes INFO@LUXXBOX.COM WWW.LUXXBOX.COM















TYPE:


DRIVER INFORMATION

			WATTAGE (W)		MAX VOLTAGE	COMPLIANCE	
REGION/DIMMING	SIZE	D OR I	DI	НО	(V)	COMPLIANCE	
UNIVERSAL (UNV) 0-10V - 1% dimming	SMALL	24W	-	-	- 10-55VDC	FC c(VL)us	
110 - 277VAC (North America only)	MEDIUM / LARGE	58.9 W	54.5 W	58.9 W	10-55VDC	LISTED	
GLOBAL (G) 0-10V - 1% dimming	SMALL	24W	-	-	C FOVDC	DALI & CB	
220 - 240VAC DSI DALI	MEDIUM / LARGE	45.6W	45.6W	45.6W	6-52VDC	△ (€ ②	

CANOPY INFORMATION

Please note power cord and canopy will always be supplied in black unless specified otherwise.

				UNIVERSAL (UNV)	GLOBAL (G)		
PRODUCT	SIZE	OUTPUT	CD	RD	E26	RD	E27
	SMALL	D	CDE	SA5	SA5	SB1 SI	
LX-VEC	LX-VEC MEDIUM / LARGE	D / DI	CD5				SB1
		НО	CD9R				



Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. February 2024 . LX-Vapor-Echo-Cylinder.V2 v5.00

















TYPE:

MATERIAL SPECIFICATIONS

COLOR FASTNESS TO LIGHT: ISO 105-B02-1994 Rating: 6-7		
FIRE TEST: AS 1530.3 / ISO 9705: Group 1 / GB8624 B1 / ASTM E-84-14 (Class A, FSI:20 - SDI:450) / BS EN13501-1:2007+A1:2009 (B-s1, d0)		
ENVIRONMENTAL: PET achieves GreenTag Certification / GreenRate: Level A		
THERMAL TRANSITION:	ASTM C518-2010. R- Value = 0.30 m ² K/W	
SOUND ABSORPTION: AS ISO 354 – 2006 / Noise reduction coefficient (NRC) = 0.85		
VOC EMISSIONS:	ASTM D5116 Rate: < 0.01 mg/m²/hr (7 days)	


Please note some of these certificates will apply to specific colors.

PRODUCT ACOUSTIC PROPERTIES


Testing and post analysis procedures were carried out in accordance with the references detailed below:

AS ISO 354-2006 (R2016)	Acoustics—Measurement of sound absorption in a reverberation room
AS ISO 11654—2002	Rating of sound absorption—Materials and systems
ASTM C423-17	Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method
ASTM E795-16	Standard Practices for Mounting Test Specimens During Sound Absorption Tests
ISO 20189	Screens, furniture and single objects intended for interior use – Rating of sound absorption and sound reduction of elements based on laboratory measurements.

S	Frequency (Hz)	Sound Absorption Coeficient	SMALL (S)	MEDIUM (M)	LARGE (L)
B	125	0.06	0.50	1.02	2.02
SAI	250	0.33	2.77	5.62	11.12
ΑL	500	0.73	6.13	12.42	24.60
ERI	1000	1	8.39	17.02	33.69
МР	2000	0.96	8.06	16.34	32.35
_	4000	1	8.39	17.02	33.69



	Frequency (Hz)	Sound Absorption Coeficient	SMALL (S)	MEDIUM (M)	LARGE (L)
S Z	125	0.06	0.05	0.09	0.19
AB	250	0.33	0.26	0.52	1.03
ر ر	500	0.73	0.57	1.15	2.29
Y	1000	1	0.78	1.58	3.13
∐ ∑	2000	0.96	0.75	1.52	3.01
	4000	1	0.78	1.58	3.13



The Sabin data shown above is in accordance with the latest International Standards for the rating of sound absorption and reduction. This is different from the classic methodology, which includes the calculation of the Noise Reduction Coeficient (NRC), the Sound Absorption Average (SAA), the Weighted Sound Absoption Coefficient (aw) and the Sound Absorption Class (SAC). However, to make it easier to compare against other products, we are including that information on the table on the right, which was calculated using the Horizontal Floor Area method. Fully detailed test reports are available upon request.

NRC	0.75
SAA	0.75
aw	0.60
SAC	С

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal, February 2024, LX-Vapor-Echo-Cylinder, V2 v5.00




















TYPE:


PRODUCT DIMENSIONS

TOP VIEWS


SIDE VIEWS


SMALL







MEDIUM





LARGE





Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. February 2024 . LX-Vapor-Echo-Cylinder.V2 v5.00



